



## DECLARATION of PERFORMANCE

No. 18916

1. Unique identification code of the product type:  
**Aggregate Concrete Masonry Unit 7.3N Medium Dense Coursing Brick**
2. Intended use: **Walls, columns and partitions**
3. Manufacturer:  
**Mansfield Brick Company Ltd.**  
**Crown Farm Way**  
**Forest Town**  
**Mansfield**  
**Nottinghamshire**  
**NG19 0FT**
4. AVCP: **System 4**
5. Harmonised Standard: **EN 771-3:2011 +A1:2015**
6. Declared performance:

Essential characteristics		Performance
Dimensions	Length mm	215
	Width mm	100
	Height mm	65
	Tolerance Category	D1
Configuration		Group 1
Compressive strength	Mean	7.3N/mm <sup>2</sup>
	Direction of Load	Perpendicular to bed face
	Unit category	Category 11
Dimension Stability		NPD
Bond strength	Shear bond strength	NPD
	Flexural bond strength	NPD
Reaction to fire		Euroclass A1 (Commission Decision 2000/605/EC)
Water Absorption		NPD
Water vapour permeability		NPD
Direct airborne sound insulation		
Gross Density		1,500 kg/m <sup>3</sup>
Configuration; dimensions and tolerances		Group 1
Thermal resistance		NPD
Durability against freeze/thaw		NPD

The performance of the product identified above is in conformity with the declared performance. This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011 under the sole responsibility of the manufacturer.

Signed for and on behalf of the Mansfield Sand Company Ltd:

Andrew Ward  
Technical Manager

...*A. Ward*.....  
01.06.17



**Mansfield Sand Company Ltd (Brick Division).  
Crown Farm Way, Forest Town, Mansfield, Nottinghamshire, NG19 0FT**

**13**

**18916**

**EN 771-3:2011 +A1:2015**

**Product: Aggregate Concrete Masonry Unit 7.3N Medium Dense Coursing Brick**

**Intended use: Walls, columns and partitions**

**Dimensions: L:215mm, W:100mm, H:65mm**

**Dimension tolerances:**

**Category: D1**

**Configuration: Group 1**

**Compressive strength: mean 7.3N/mm<sup>2</sup>**

**Reaction to fire: Euroclass A1**

**Water Absorption: NPD**

**Water vapour diffusion: NPD**

**Direct airborne sound insulation:**

**Gross dry density: 1,500 kg/m<sup>3</sup>**

**Configuration: Group 1**

**Durability against freeze/thaw: NPD**